


ATXBlade AB220 Xeon blade node Specifications



Form Factor

Open ATX form factor, certified with the Tyan S2725 Dual Xeon Server Board

Dimensions and Color

1.75" (height) x 13.5" (width) x 20" (depth); silver color

Drive Support

Two 3.5-inch one-inch height hard-disk bays

System Cooling

Six 120mm hot-air-exhaust fan on the ATXBlade housing unit

Front Panel

Buttons & Switches	Power
LEDs	Power, hard-drive activity, Network activity

Environment

Ambient Temperature	Operating (system): 0°C to +35°C, with maximum change not to exceed 10°C; non-operating (system): -40°C to +70°C
Relative Humidity	Non-operating; 90% @ 35°C non-condensing
Shock	Operating: 2 millisecond (half sine wave) @ 5G; Non-Operating: 2 millisecond (half sine wave) @ 10G
ESD	15kV



Rackmount.com, Inc.
134 Linden Avenue, Suite 200
Westbury, NY 11590
Tel: 516-997-5050 Fax: 516-997-5784
<http://www.atxblade.com>

Standard Power Supply

AC Power Supply One fixed 350 Watts non-redundant (110/220v auto switch)

Power Consumption 288 Watts (Typical)

Processor Support

Dual 2.4Ghz – 2.8Ghz Intel® Xeon processor 512K or 1M Cache (Socket 604 / 533Mhz FSB)

Hard-Drive Support

One standard 120GB ATA100/133 EIDE hard disk drive (Optional: 80GB/120GB/160GB/180GB HDD or 2nd hard disk)

Memory

Capacity Four DIMM sockets for up to 8GB (64MB to 2GB DIMMs supported)

Type Registered ECC DDR266 un-buffered SDRAM 72-bit, 184-pin gold-plated DIMMs.

Motherboard

Tyan S2725 server board based on Intel 7501 Chipset

System BIOS

4MB Flash EEPROM with Intel/AMI BIOS

Standard Port

Graphic	ATI Rage XL SVGA PCI video controller with 8MB of video memory
Network (LAN)	Two integrated Intel Gigabit ethernet Connector; Supports 10BASE-T, 100BASE-TX, and 1000BASE-TX, RJ45 output
USB	Two USB connectors at rear panel support USB 2.0
Serial	One RS-232 Serial connector
PS2	Mouse and Keyboard

Rev. A 2002